



# NEMO™ “Any-Density” Fiber Patch Panel

The NEMO Fiber Patch Panel is the latest advancement in the PEACOC® product family that integrates Go!Foton’s innovative spreadable adapter technology into a traditional bulkhead-style fiber panel. The result is a simple and low-cost solution that enables superior access and secure fiber management for any number or type of connection. It is ideal for today’s modern high-capacity and data-rate intensive telecommunication and data communication networks. **Network Enhanced Manageable Optics:** It’s “any-density” fiber management – *that works!*

## Benefits:


- Easy Access: NEMO spreadable adapter technology that minimizes insertion loss while providing generous access to all connectors
- Scalable Density: From 6 ports (single rail) to 72 ports (fully loaded) and anything in between
- Versatile: Supports a variety of connector types from LC to SC to MPO and more
- Universal: Mounts in any 19” or 23” rack, frame, cabinet, or wall mount bracket
- Flexible: Supports basic patch panel functionality and pre-terminated cabled panels
- Cost Effective: Simple, lightweight design

## Features:

- Adapters safely and effortlessly spread apart using NEMO technology
- Field expandable – can mix and match connector types as you grow
- Convenient port labelling for each connection on both front and rear sides of the panel
- Optional front and rear protective doors with ample space for circuit identification
- Available with a variety of options for cable management on the front and rear sides

## Applications:

- Datacenter Networks
- Enterprise Networks
- Telecommunication Networks
- Wireless Networks
- Fiber Management and Distribution Frames
- Outdoor Cabinets & Enclosures



NEMO 1RU 72 PORT



NEMO “ANY-DENSITY”

SPREADABLE ADAPTERS



EASY ACCESS TO ANY CONNECTOR



CONVENIENT PORT IDENTIFICATION




# NEMO™ Fiber Patch Panel

## Specifications:


PARAMETER	SPECIFICATION
Max Number of Ports Per 1RU	Duplex LC: 72 Ports (144 fibers) Simplex SC: 72 Ports (72 fibers) MPO: 72 Ports (72 x 8, 12, or 24 fibers)
Height	1RU (~1.75")
Width	19" Rack (default) 23" Rack (with available adapter brackets)
Depth	10.8" (with both front & rear cable hangers)
Total Weight (full port capacity)	2.3lbs (1.04kg)
Operating Temperature	-40°C to +65°C
Cable Type(s)	Any: 1.2mm, 1.6mm, 2mm, 3mm, 3.8mm, etc...
Standards	GR-449

## Product Dimensions:



# NEMO™ Fiber Patch Panel

## Ordering Guide:



PRODUCT FAMILY	
Code	Code Description
P	PEACOC

PRODUCT TYPE	
Code	Code Description
N	NEMO

NO. OF RUs	
Code	Code Description
1	1RU
X	Single Rail

TYPE OF PORTS	
Code	Code Description
L	LC Duplex
S	SC Simplex
P	MPO (8/12/24)
X	None (Empty Panel)

PORT COLOR	
Code	Code Description
B	Blue
E	Beige
K	Black
G	Green
Q	Aqua
V	Violet

NO. OF PORTS	
Code	Code Description
012	12 Ports
016	16 Ports
024	24 Ports
032	32 Ports
036	36 Ports
048	48 Ports
064	64 Ports
072	72 Ports
---	3 Digit Code

REAR CONNECTION / INNER CABLING	
Code	Code Description
X	None (Patch Panel Only)
P	Pre-term Pigtail

PRODUCT SERIES	
Code	Code Description
---	Product Series (3 numbers)

CUSTOMER CODE	
Code	Code Description
---	Customer Code (3 letters)

DOORS	
Code	Code Description
1	Front & Rear
2	Front Only
3	Rear Only
X	None

CABLE MANAGEMENT	
Code	Code Description
1	Front & Rear (Side Exit)
2	Front (Side Exit) + Rear (Rear Exit)
3	Front Only (Side Exit)
4	Rear Only (Side Exit)
5	Rear Only (Rear Exit)
X	None

PORT LABELS	
Code	Code Description
A	Port Number
B	Fiber Number / Count
D	Letters (By Port)
C	Custom
X	None

FRONT FIBER MODE / POLISH	
Code	Code Description
X	None (Patch Panel)
1	Single Mode / UPC
2	Single Mode / APC
3	Multimode OM3 / PC
4	Multimode OM4 / PC
C	Custom