


Optical Fiber Amplifier **pOA⁺** PICO EDFA PLUS

The world smallest EDFA, pOA⁺ is a full-functioning EDFA module with the control circuit packaged inside. It is designed for a single wavelength applications in full extended c-band fiber optic communications system in core networks, access networks, or CATV networks. The pOA⁺, OFA-TCQ series provides very stable output power up to in C-band over the wide operating temperature range. Ultra compact size (59 x 16 x 7.5 mm), combined with the extremely low power consumption, allows the OFA-TCQ series to be highly suitable for applications of power equalization or pre-emphasis in densely packaged telecom systems, especially for densely integrated high speed transmitter or receiver cards and loss compensation for compact active optical module.



Features

- Ultra compact size (59 x 16 x 7.5 mm)
- Full functional EDFA module including micro process control circuit
 - Including VOA, TOF, VOA+TOF, GFF (Optional)
 - Automatic wavelength searching and locking function (Optional)
 - Including Input Monitor and Input Isolator (Optional)
 - Extremely low power consumption over wide operating temperature range
 - Wide operating wavelength range
 - Wide settable output power range
 - APC (Automatic Power Control) with FLS (Forced Laser Shutdown)
 - Control & monitoring by I2C
 - LVTTTL Alarm
 - Single + 3.3 V power supply

Applications

- Optimized for integration into 100 Gbps coherent CFP & CPF2 modules
- Loss Compensation for active optical modules
 - Power boosting and Pre-emphasis Amplifier for DWDM Metro System
 - 2.5G/10G/40G/100G Channel Amplifier
 - ROADM System
 - CATV System

Optical Fiber Amplifier

PICO Optical Amplifier Plus

Optical Characteristics

Parameter	Symbol	Specification			Unit
		w/ TOF+VOA	w/o TOF+VOA	w/ GFF	
Signal wavelength range	λ	1527.99~1568.36			nm
Operating input power	P_{IN}	-20 ~ 5	-30 ~ 5	-30 ~ 5	dB
Saturation output power ⁽¹⁾	P_{OUT}	Max.12	Max.17	Max.12	dBm
Small signal gain ⁽²⁾	G	-	Typ. 30	Typ. 30	dBm
In-band OSNR ⁽³⁾	OSNR _i	Min. 41	Min. 41	Min. 41	dB
Out-band OSNR ⁽³⁾	OSNR _o	Min. 41	Min. 35	Min. 38	dB
Noise figure	NF	Typ. 6.0			dB
Filter tuning range	FTR	1528~1568	-	-	dB
Attenuation range	VOA	Min. 20	-	-	nm
Optical isolation	ISO	Min. 20			dB
Return loss	RL	Min. 40			dB
Polarization mode dispersion	PMD	Max. 0.5			dB
Polarization dependent gain	PDG	Max. 0.5			ps


(1) Input Power = 0dBm

(2) w/ TOFA+VOA : Input Power = -30dBm, Pout≥0dBm at 1545 nm

w/o TOFA+VOA : Input Power = -30dBm, Pout≥+7dBm at 1545 nm

(3) Input Power = -10dBm at optimized output power, Pout≥0dBm, with operating wavelength range

Mechanical Dimension (59 x 16 x 7.5[mm] with IPM)



* The location of optical input port depends on the option of including IPM

Electric & Environmental Characteristics

Parameter	Typical Value
Power supply voltage ⁽¹⁾	+3.3 V
Interface	I2C
Alarm	LVTTL
Operating case temperature	-5 ~ 75 °C
Storage temperature	-40 ~ 85 °C
Storage humidity	5 ~ 85 % R.H
Power consumption ⁽²⁾	≤ 1.8 W

(1) Additional power supply voltage required for TOF/VOA option.

(2) at Max. output power in normal input power = 0dBm and full temperature range
Max. P_{Tot} is less than 1.0W at Pout=+10dBm or less.

Control and Monitoring Functions

Parameter	Typical Value
Control Scheme	APC with FLS* (AGC optional)
Monitor	IPM(Optional) / OPM / LD-Bias / Case-Temp
Alarm	LOS(Optional) / LOP / LD-Bias / Case-Temp

* FLS: Forced Laser Shutdown

Ordering Information

Part Number	Description
OFA - TCQ - xx ₁ AP - yy ₁ yy ₂ - zz ₁	Ordering code structure
xx ₁	: Max. Output Power (dBm)
yy ₁	: NA(Not available), VA(VOA), TF(TOF), AF(VOA+TOF), GF(GFF)
yy ₂	: I(IPM), Not available without IPM
zz ₁	: LU(LC/UPC), LA(LC/APC)

LiComm Co., Ltd.

Address

109, Baekja-ro Idong-myeon, Cheoin-gu, Yongin-Si,
Gyeonggi-Do, 17126, Korea

Tel: +82-31-323-1926, 1936 Fax: +82-31-323-2447

E-mail: sales@licomm.com Website : www.licomm.com